



STR-21G-S0 Solar Monitoring Systems

Technical Specifications

Turnkey Solar Monitoring Station

DNI measurements

ISO 9060 Secondary standard sensor

Low power consumption

ISO 17025 calibration

EKO's new solar Monitoring System, the STR-21G-S0, is a turnkey sensor system to perform the most accurate solar radiation measurements of the direct solar radiation component. It can be easily integrated to any DAQ system, which has multiple analog or digital inputs. With the standard sun-position sensor and GPS receiver built inside the sun tracker, the system set-up will be quick and easy.

The system is based on the STR-21G Sun tracker and in combination with the MS-57 First class pyrheliometer. The STR-21G-S0 system can be freely configured to measure the required Solar radiation components in the most accurate way. The MS-57 pyrheliometer has a heated front window to avoid condensation and ice which can affect the measurements.

Unique to the system, EKO's radiometers have the ability to sample much faster than traditional solar sensors. Faster sample rates allow the sensor to

'catch' more accurately the peak irradiance value under variable atmospheric conditions and lower the measurement uncertainty of one minute averaged values.

	STR-21G-S0
Sun Tracker	STR-21G-SET
Pyrheliometer	MS-57-SET-10-P-MR

	STR-21G
Arms	1
Pointing accuracy Solar elevation: 0 to 87°	< 0.01 °
Angle resolution	0.009 °
Rotation angle Zenith	-15 - 95 °
Rotation angle Azimuth	0 - 360 °
Torque	12 Nm
Payload side arms	7.5 kg (Total payload 15kg)
Sun sensor FOV	30 °
Ingress protection IP	65
Operating temperature range	-40 - 60 °C
Communication	RS-422 / 232C
Power consumption	< 10 W
Power supply	21 to 31 VDC / 15W
Power supply (Power Adapter)	100 to 240 VAC / 20W
Dimensions mm	430 (W) x 380 (L) x 440 (H)
Weight	14.5 kg (With tripod)
Motor	Stepper motor
Driving technology	Harmonic drive®
Tracking mode	Solar position / Free positioning

Tripod	Table tripod
Pyrheliometer mount	Adjustable / One position
Cable length	10 m

Options	STR-21G
Cable length Power cable	20 / 30 m
Cable length Communication cable	5 / 10 m
Shading assembly Disk	MD-81-10 (MS-80)
Top mounting plate A (1 position)	TMP-S-(sensor model)
Top mounting plate B (2 positions)	TMP-D-(sensor model)

	MS-57
ISO 9060:2018	Class A
ISO 9060:1990	First Class
Sub-category "Spectrally flat"	Compliant
Sub-category "Fast response"	Compliant
Output	Analog (mV)
Response time 95%	< 0.2 Sec.
Zero off-set a) 200W/m ²	0 W/m ²
Zero off-set b) 5K/hr	< 1 W/m ²
Complete zero off-set c)	< 1 W/m ²
Non-stability change/1 year	-
Non-stability change/5 years	< 0.5 %
Non-linearity at 1000W/m ²	< 0.2 %

Spectral error	+/- 0.2 %
Temperature response -20°C to 50°C	< 0.5 %
Tilt response at 1000W/m²	< 0.2 %
Sensitivity	Approx. 7 μV/W/m ²
Impedance	< 15000 Ω
Operating temperature range	-40 - 80 °C
Irradiance range	0 - 4000 W/m ²
Wavelength range	200 - 4000 nm
Ingress protection IP	67
Cable length	10 m

Options	MS-57
Cable length	20 / 30 m

Specifications are subject to change without further notice.