



## STR-21G-S0 Solar Monitoring Systems

### Technical Specifications

Turnkey Solar Monitoring Station

DNI measurements

ISO 9060 Secondary standard sensor

Low power consumption

ISO 17025 calibration

EKO's new solar Monitoring System, the STR-21G-S0, is a turnkey sensor system to perform the most accurate solar radiation measurements of the direct solar radiation component. It can be easily integrated to any DAQ system, which has multiple analog or digital inputs. With the standard sun-position sensor and GPS receiver built inside the sun tracker, the system set-up will be quick and easy.

The system is based on the STR-21G Sun tracker and in combination with the MS-57 First class pyrheliometer. The STR-21G-S0 system can be freely configured to measure the required Solar radiation components in the most accurate way. The MS-57 pyrheliometer has a heated front window to avoid condensation and ice which can affect the measurements.

Unique to the system, EKO's radiometers have the ability to sample much faster than traditional solar sensors. Faster sample rates allow the sensor to

'catch' more accurately the peak irradiance value under variable atmospheric conditions and lower the measurement uncertainty of one minute averaged values.

	<b>STR-21G-S0</b>
Sun Tracker	STR-21G-SET
Pyrheliometer	MS-57-SET-10-P-MR

	<b>STR-21G</b>
Arms	1
Pointing accuracy Solar elevation: 0 to 87°	< 0.01 °
Angle resolution	0.009 °
Rotation angle Zenith	-15 - 95 °
Rotation angle Azimuth	0 - 360 °
Torque	12 Nm
Payload side arms	7.5 kg (Total payload 15kg)
Sun sensor FOV	30 °
Ingress protection IP	65
Operating temperature range	-40 - 60 °C
Communication	RS-422 / 232C
Power consumption	< 10 W
Power supply	21 to 31 VDC / 15W
Power supply (Power Adapter)	100 to 240 VAC / 20W
Dimensions mm	430 (W) x 380 (L) x 440 (H)
Weight	14.5 kg (With tripod)
Motor	Stepper motor
Driving technology	Harmonic drive®
Tracking mode	Solar position / Free positioning

<b>Tripod</b>	Table tripod
<b>Pyrheliometer mount</b>	Adjustable / One position
<b>Cable length</b>	10 m

<b>Options</b>	<b>STR-21G</b>
<b>Cable length Power cable</b>	20 / 30 m
<b>Cable length Communication cable</b>	5 / 10 m
<b>Shading assembly Disk</b>	MD-81-10 (MS-80)
<b>Top mounting plate A (1 position)</b>	TMP-S-(sensor model)
<b>Top mounting plate B (2 positions)</b>	TMP-D-(sensor model)

	<b>MS-57</b>
<b>ISO 9060 classification</b>	First Class
<b>Output</b>	Analog (mV)
<b>Response time 95%</b>	< 0.2 Sec.
<b>Zero Offset A 200W/m<sup>2</sup></b>	0 W/m <sup>2</sup>
<b>Zero Offset B 5K/hr</b>	< 1 W/m <sup>2</sup>
<b>Non-stability change/1 year</b>	-
<b>Non-stability change/5 years</b>	< 0.5 %
<b>Non-linearity at 1000W/m<sup>2</sup></b>	< 0.2 %
<b>Spectral selectivity 0.35-1.5µm</b>	+/- 1 %
<b>Temperature response -20°C to 50°C</b>	< 0.5 %
<b>Tilt response at 1000W/m<sup>2</sup></b>	< 0.2 %
<b>Sensitivity</b>	Approx. 7 µV/W/m <sup>2</sup>

<b>Impedance</b>	< 15000 Ω
<b>Operating temperature range</b>	-40 - 80 °C
<b>Irradiance range</b>	0 - 4000 W/m <sup>2</sup>
<b>Wavelength range</b>	200 - 4000 nm
<b>Ingress protection IP</b>	67
<b>Cable length</b>	10 m

<b>Options</b>	<b>MS-57</b>
<b>Cable length</b>	20 / 30 m

Specifications are subject to change without further notice.