



STR-22G Sun Trackers

Technical Specifications

Double arm Sun tracker

GPS for easy and accurate set up

Standard Integrated Sun sensor

Power consumption less than 10W

RS-232 serial interface for position control

The compact 2 arms sun tracker is perfectly suited to support all kinds of Global, Diffuse and Direct Radiation measurement sensors. Besides the standard EKO sensor mounts, various alternative mounts for non-EKO sensors are available. EKO Instruments improved the STR-22G Sun Tracker with a fully automated set up procedure through a GPS receiver, providing increased reliability and enhanced functionality.

From sunrise to sunset the compact Sun-Tracker guarantees accurate sun tracking and pointing of the attached solar sensors. The 2-axis tracker automatically adjusts to the sun's position by the sun sensor closed-loop control system, even if the tracker is not oriented or leveled properly.

The sun-tracker comes standard with a small table tripod (larger tripod available). The 24 VDC low power consumption tracker can be powered by a solar-powered battery system or DC power supply. A

wide range AC power adapter can be supplied to connect to the grid.

For over 20 years our clients who have deployed the STR sun-tracker, experience ease of set-up, operating and reliable tracking.

	STR-22G
Arms	2
Pointing accuracy Solar elevation: 0 to 87°	< 0.01 °
Angle resolution	0.009 °
Rotation angle Zenith	-15 - 95 °
Rotation angle Azimuth	0 - 360 °
Torque	24 Nm
Payload side arms	15 kg
Sun sensor FOV	30 °
Ingress protection IP	65
Operating temperature range	-40 - 50 °C
Communication	RS-422 / 232C
Power consumption	< 10 W
Power supply	21 to 32 VDC / 20W
Power supply (Power Adapter)	100 to 240 VAC / 20W
Dimensions mm	430 (W) x 380 (L) x 440 (H)
Weight	15.5 kg (With tripod)
Motor	Stepper motor
Driving technology	Harmonic drive®
Tracking mode	Solar position / Free positioning
Tripod	Table tripod
Pyrheliometer mount	Adjustable / One position
Cable length	10 m

Options	STR-22G
Cable length Power cable	20 / 30 m
Cable length Communication cable	5 / 10 m
Top mounting plate A (1 position)	TMP-S-(sensor model)
Top mounting plate B (2 positions)	TMP-D-(sensor model)
Shading ball assembly A (1 position)	MB-12-1
Shading ball assembly B (2 positions)	MB-12-2
Pyrheliometer mount B (2 positions)	STR-22-AD

Specifications are subject to change without further notice.